

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 679 099 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
18.07.2001 Bulletin 2001/29

(51) Int Cl.7: **A61M 1/00, F04B 43/08,
F04B 43/12, A61M 1/34**

(21) Application number: **95902600.6**

(86) International application number:
PCT/US94/13320

(22) Date of filing: **16.11.1994**

(87) International publication number:
WO 95/13837 (26.05.1995 Gazette 1995/22)

(54) **PERISTALTIC PUMPING ASSEMBLY**
PERISTALTISCHE PUMPENANORDNUNG
ENSEMBLE POMPE PERISTALTIQUE

(84) Designated Contracting States:
BE DE FR GB IT

• **TSUJI, Tsuyoshi**
Ohmiya (JP)

(30) Priority: **17.11.1993 US 153615**

(74) Representative: **MacGregor, Gordon et al**
Eric Potter Clarkson,
Park View House,
58 The Ropewalk
Nottingham NG1 5DD (GB)

(43) Date of publication of application:
02.11.1995 Bulletin 1995/44

(73) Proprietor: **BAXTER INTERNATIONAL INC.**
Deerfield, IL 60015 (US)

(56) References cited:
FR-A- 2 396 880 **US-A- 382 096**
US-A- 4 473 342 **US-A- 4 886 431**
US-A- 5 096 393 **US-A- 5 098 261**

(72) Inventors:
• **CHAPMAN, Arthur, S.**
Solvang, CA 93461 (US)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 679 099 B1

Description

Field of the Invention

[0001] The present invention relates to peristaltic pumps and related apparatus. More particularly, the invention relates to compact peristaltic pumps and related apparatus suitable for providing compact pumping equipment such as a portable hemapheresis device.

Background of the Invention

[0002] Various automated hemapheresis systems for separating whole blood into two or more of its constituents have been utilized in the past. Such devices are shown in US-A-4,851,126 and US-A-5,188,588.

[0003] Such systems are adapted for blood cell separation generally and often specifically for platelet separation. In general, such systems collect whole blood from the donor, separate the desired cells and return the remaining blood components to the donor usually through a single needle. Although a separate return needle can be used, it is preferred that a single venepuncture needle be used both for collection and reinfusion. Hemapheresis systems generally include a disposable set of bags, reservoirs and conduits. The use of peristaltic pumps to cause the blood fluids to move through the system is preferred because the blood and separated blood components can be moved through the device while it is wholly contained within the sterile disposable components, which are commonly referred to as a harness set. Harness sets include, at least, one venepuncture needle, at least one separation device for separating blood into its components, and at least one reservoir for containing blood. A plurality of conduits connects the needle, the separation device and the reservoir to each other. The conduits include a section formed of flexible elastomeric material so that blood can be moved through the conduits by means of peristaltic roller pumps.

[0004] The preferred type of system includes, as a minimum, a single venepuncture needle, separation means for separating at least one constituent from whole blood, first and second reservoirs containing blood, a first conduit interconnecting the needle and the first reservoir, a second conduit interconnecting the first reservoir and the separation means, a third conduit interconnecting the separation means and the second reservoir, and a fourth conduit for returning blood components to the needle. Preferably, four separate peristaltic pumps are provided to move the blood and the blood components through the conduits.

[0005] Typically, systems of this general type also include a microprocessor for controlling a number of pumps, clamps, detectors, monitoring systems, et cetera, for automating the collection of whole blood from the donor, separating the blood into plasma and cell concentrate, collecting the plasma and reinfusing the cell

concentrate into the donor using the harness set applied to the instrument. After application of venepuncture to the blood donor, the instrument operates between alternating collection and reinfusion cycles. In the collection cycle, anticoagulated whole blood is pumped by a blood pump to the separator of the harness where it is separated into plasma which flows into a collection container and cell concentrate which flows to a reinfusion reservoir. In the reinfusion cycle, the blood pump reverses to flow cell concentrate from the reservoir through the phlebotomy needle to the donor.

[0006] Peristaltic pumps are also used for the delivery of other liquids such as medications, additives to fluid mixing processes, etc. A need has continued to exist for such apparatus that is compact and easy to use.

[0007] US-A-3832096 discloses a peristaltic pump having a single rotor with sections for engaging separate lengths of tubing. The whole rotor is fixed to a driven shaft.

[0008] US-A-4886431 also discloses a peristaltic pump having a single rotor with sections for engaging separate lengths of tubing. The races are individually separable from the sections.

[0009] FR-A-2 396 880 discloses a pelistaltic pump having a single motor and at least two rotors each being selectively engageable to the single motor by means of an engagement mechanism.

[0010] The present invention provides a pumping module assembly comprising at least two axially aligned peristaltic pumping rotors rotatably carried side by side on a single axle,

a race aligned with each of the pumping rotors to engage flexible tubing to cause peristaltic flow upon rotation of the rotors,
a separate motor associated with each of the peristaltic pumping rotors, and
a drive mechanism for operatively connecting each of the pumping rotors to a different one of the motors.

[0011] In a preferred embodiment, at least one of the races is individually releasable from its associated rotor so that the pumping action of its associated rotor can be independently interrupted without interrupting the pumping action of the other rotors.

[0012] In a preferred embodiment, the entire pumping module can be removable as a unit for service, repair, or replacement.

[0013] Reference is made to the following drawings.

Brief Description of the Drawings

[0014]

Figure 1 is a perspective view of a portable auto-pheresis device of the present invention with the cover in the closed position;

Figure 2 is a top plan view of an embodiment of a harness set usable in connection with the present invention;

Figure 3 is a front elevational view of a device in accordance with the invention with the pump module cover in the closed position and illustrating the open position of the cover by means of phantom lines;

Figure 4 is an end view of the device of Figure 3;

Figure 5 is a perspective view of a device in accordance with the invention with the harness set installed;

Figure 6 is a cross-sectional view of a pump module assembly in accordance with the invention taken the central shaft of the assembly;

Figure 7 is a cross-sectional view taken along line 7-7 of Figure 6;

Figure 8 is a cross-sectional view taken along line 8-8 of Figure 6;

Figure 9 is a cross-sectional view taken along line 9-9 of Figure 8;

Figure 10 is a fragmentary sectional view of a pump assembly taken along line 10-10 of Figure 6 with blood flow tubing added and with an individual release mechanism in the open position;

Figure 11 is a fragmentary cross-sectional view taken along line 10-10 of Figure 6 showing the individual release mechanism in the closed position, also showing the blood flow tubing;

Figure 12 is a perspective view of the pump module assembly and organizer frame components of the invention shown separated from each other for clarity;

Figure 13 is a top plan view of the pump module assembly showing the organizer and blood tubes in place over the pumps;

Figure 14 is a top plan view showing tubing clamps used in the device of the invention;

Figure 15 is a cross-sectional view taken along line 15-15 of Figure 14; and

Figure 16 is a cross-sectional view taken along line 16-16 of Figure 15.

Detailed Description of the Drawings

[0015] Referring now to the drawings, there is illustrated a portable autopheresis device, generally designated 10. Device 10 includes a bottom portion 12 and a cover portion 14 hinged along an axis 16. A carrying handle 18 is provided which is hingedly connected to bottom portion 12 at hinge points 19.

[0016] Referring to Figure 2, there is illustrated a disposable tubing or harness set generally designated 20. In accordance with the invention, harness set 20 is applied to the hemapheresis device 10 as illustrated in Figure 5 to effect collect of whole blood from a donor through a single needle, separation of the whole blood into packed blood cells and platelet poor plasma, and

reinfusion of the packed blood cells to the donor.

[0017] Tubing set 20 is provided with a single venepuncture needle set 22 for alternately receiving whole blood from a donor and reinfusing packed cells into the donor. Venepuncture needle set 22 communicates with a blood line 24. An anticoagulant line has an anticoagulant spike 18 at one end for reception in an anticoagulant supply container 30 illustrated in Figure 5. At its opposite end, anticoagulant line 26 joins blood line 24 in a Y-connection closely adjacent the single venepuncture needle 22.

[0018] Tubing set 20 also includes a reservoir 32. Blood line 24 is connected through port 38 at the lower end of the reservoir 32. Tube 44 extends into reservoir 32 through an inlet port 48 at the upper end of reservoir 32. Blood line 24 branches at a Y-connection 50 to branch line 52 connecting blood line 24 with inlet port 38 of reservoir 32, and to branch line 34 connecting blood line 24 to separator inlet 60.

[0019] Tubing set 20 additionally includes a separator 56 for separating anticoagulated whole blood into packed cells and plasma. Such separators are preferably of a membrane type, known in the art. Separator 56 has a whole blood inlet port 60, a packed cell outlet port 58 and a platelet poor plasma outlet port 62. Line 64 connects the packed cell inlet port 48 of reservoir 32 with the outlet port 58 of separator 56. Conduit line 66 connects the whole blood inlet port 60 of separator 56 by means of a Y-connections as shown with tubing 24. By means of a Y-connection tubing 66 is also connected by tubing 69 to a saline bag spike 71. Lines 25 and 67 lead to pressure sensors. Tubing 68 connects between the plasma outlet port 62 of separator 56 and a plasma collection container 70.

[0020] A tubing organizer 72, which may be formed either of solid or cellular plastic material, in the form of a rectangular frame open in the middle, is provided to hold the various tubing in a desired orientation. The tubing is snapped in place into slots 74 provided in the plastic material. The segments of the various tubes interacting with the pump assembly are thus positioned in registry in relation to the pumps. The organizer can remain in place during the pumping operation; and the tubing can conveniently be removed as a unit. Preferably the organizer 72 is of an L-shaped configuration to provide physical stability and resistance to twisting. Lips 76 can be provided to snap into mating recesses in the cover of the pump assembly as further explained below.

[0021] It is further contemplated that a second, alternative, tubing set may also be employed substantially as described in U.S. Patent 4,851,126. The second tubing portion is generally utilized in order to further separate the blood into platelet concentrate and platelet poor plasma. The alternative tubing set is applied to the pump assembly of the present device in a manner similar to that described above in relation to the plasma collection tubing set described above.

[0022] Referring to Figures 3, 4 and 6-12, the pump

module assembly generally identified by numeral 100 is shown in greater detail. A housing 102 is provided within bottom portion 12 of the hemapheresis device. Housing 102 is provided with a cover 104 pivotally attached to a bracket 105. Cover 104 is releasably locked in a closed position by means of handle 106 provided with a clevis 108 that engages opposite ends of a pin 110. Mounted in the upper part of housing 102 are a series of peristaltic pump rotor assemblies 112, 114, 116 and 118, hereinafter referred to as "pumping modules", all of which are mounted on a single axle 122. Each of these pumping modules is provided with a plurality of rollers 120, of which there are four in the illustrated embodiment. Shaft 122 is journaled at its opposite ends in a bearing structure 124 provided at opposite ends of housing 102. Each of the rollers 120 is outwardly biased by compression springs 126.

[0023] As seen in Figure 6, the roller pump rotors may each be formed of two-part sheaves to which drive gears 128 are bolted. Releasable race surfaces 130 and stationary race surfaces 131 are provided to backstop the blood flow conduits when they are worked on by rollers 120 as best seen in Figures 10 and 11. The compression of the flexible tubes by the rollers 120 of the pumps provides a peristaltic pumping action which moves fluid through the conduits. Reversible DC motors 132, 134, 136 and 138 (not shown) are provided to reversibly drive each of the pumping modules 112, 114, 116 and 118. Gears 140 are attached to the motor shafts 142. Each of the gears 140 meshes with a driven gear 144 each of which are mounted on shafts 146 journaled for rotation through a supporting bracket 147. Gears 144 in turn drive gears 152 which are mounted on shafts 154 which are journaled for rotation through end walls 148 of housing 150. At the opposite ends of shafts 154 are mounted drive gears 156 which mesh with and drive gears 128 on each of the pumping modules.

[0024] While the embodiment shown in the drawings illustrates the same gear ratios between each of the motors and its respective pumping module, it will be apparent that the gear ratios can be varied if it is desired that one of the pumping modules 112, 114, 116 or 118 be driven at a speed different from that of the other of said pumping modules. Also it is contemplated that a different number of pumps, for example 2 or 6 can be incorporated into the pump assembly. An assembly of four pumps is shown solely for purposes of illustration.

[0025] By opening lever 106 the axle 122 and each of the pumps mounted on it can be removed as a unit as best seen in Figure 12. For example, in the event of a blood spill the entire assembly can be removed with one hand for cleaning, or otherwise, for maintenance. Additionally, each of the concave race surfaces 130 can be individually released as shown in Figures 8, 10 and 11. Individual release mechanisms are provided by the use of release handles 160 which are pivotally attached to a rod 162 carried on cover 104. An eccentric end 164 of lever 160 bears against the upper surface of each indi-

vidual member 132, the lower end of which forms race 130. Thus, when the lever 160 is in the closed position illustrated in Figure 11, the roller 120 flattens conduit 44 between the roller and race surface 130, thus causing blood to be moved through conduit 44 in peristaltic fashion as the roller 120 is advanced. In the released position shown in Figure 10, the flow of blood through conduit 44 can be interrupted. The ability to individually release the pumping modules is useful for system fault isolation, emergencies, and other non-programmed operational modes.

[0026] The relationship of organizer 72 with the pump module assembly 100 is best seen by referring to Figures 12 and 13. An internal cover 133 is positioned over pump module assembly 100. Internal cover 133 has a series of openings 135 through which the rollers 120 are exposed. Indented channels 134 are aligned with openings 135 to receive the various blood tubes. Additional indented grooves 136 are provided over the entire transverse width of cover 133 to accommodate blood tubing that is not to be engaged or acted on by any of the peristalsis pumps. Cover 133 is further provided with exterior shoulders 138 that closely interfit with the interior surfaces of organizer frame 72. Placement of the frame 72 over cover 133, thus, provides a mating fit by virtue of which the blood tubes are placed in precise registry with grooves 133 of 4 or 136, as required. Organizer frame 72 is provided with projecting lips 76 that engage recesses 140 at the opposite ends of cover 133 to positively allow the organizer frame 72 to be snapped and held in place.

[0027] In addition to pump module assembly 100, cover 104 overlies projecting element 80 that is provided with a series of slots 82. Slots 82 are provided with lateral openings 83 which accommodate clamp fingers 84 that, if required, can clamp off conduits 34, 52 and 68 as seen in Figures 14-16. Fingers 84 can be operated by rocker arms 88 and 89 which are actuated by solenoid valves 86 and 87 are each controlled by software that operates each of the successive operations of apparatus 10. Thus, for example, when blood is being re-injected into the patient, tubing 34 is clamped closed so that saline solution cannot enter tubing 24. Similar clamping or unclamping steps will be apparent to those skilled in the art.

[0028] It will be noted in connection with the preferred embodiment that pump drive motors 134 and 136 are approximately half of the length of the pump module, thus allowing four motors to be located under the pump module assembly. The gear reduction assembly has symmetry about the center plane of the pump module assembly and is located outside of the housing 150. Shafts 154 are provided with seals to prevent blood or other fluids from entering the main body of the machine from within housing 150 in the event of a spill. It will be noted that since the pumping modules are radially removable from the gear train, they are removable for cleaning and maintenance without disturbing the bal-

ance of the equipment.

Claims

1. A pumping module assembly comprising at least two axially aligned peristaltic pumping rotors (112, 114, 116, 118) rotatably carried side by side on a single axle (122),

a race (130, 131) aligned with each of the pumping rotors to engage flexible tubing to cause peristaltic flow upon rotation of the rotors, a separate motor (132, 134, 136, 138) associated with each of the peristaltic pumping rotors (112, 114, 116, 118), and a drive mechanism (140, 144, 152, 156, 128) for operatively connecting each of the pumping rotors to a different one of the motors.

2. A pumping module assembly according to Claim 1 wherein at least one of the races (130) is individually releasable from its associated rotor (112, 114, 116, 118) so that the pumping action of its associated pumping rotor can be independently interrupted without interrupting the pumping action of the other rotors.

3. A pumping module assembly according to Claim 1 wherein the races are carried by a cover (104) that is movable to an opened position for permitting removal of the pumping rotors (112, 114, 116, 118) attached to the single axle (122).

4. A pumping module assembly according to Claim 3 wherein the cover (104) is pivotable between the closed position and the opened position.

5. A pumping module assembly according to any preceding claim wherein the drive mechanism comprises drive gears (156) driven by the motors (132, 134, 136, 138) and a driven gear (128) is attached to each of the pumping rotors and adapted to engage the drive gear, the driven gears (128) being radially separable from the drive gears (156).

6. A pumping module assembly according to any preceding claim, including a base surface, each pumping rotor (112, 114, 116, 118) carrying rollers (120) circumferentially spaced about its periphery, at least a portion of each pumping rotor extending through the base surface, the axle (122) extending parallel to the base surface with the rollers spaced radially from the axle.

7. A blood processing apparatus comprising:

an array (20) of flexible blood flow conduits for

conveying blood, a pumping module assembly (100) according to Claim 1, each rotor (112, 114, 116, 118) being engageable with the conduits for activating the flow of blood through the conduits, a housing (102) containing the pump module assembly (100), and a removable cover (104) on the housing for retaining the pump module assembly in the housing when the cover is closed and for permitting removal of the pump module assembly from the housing when the cover is opened.

8. A pumping module assembly according to Claim 6, wherein the drive mechanism comprises a shaft (154) extending through a seal positioned in a surface of the housing (102), whereby the pump module assembly (100) is separated from the motors (132, 134, 136, 138) as an integral unit.

Patentansprüche

1. Pumpenmodulbaugruppe mit mindestens zwei axial ausgerichteten, drehbar nebeneinander auf einer einzelnen Achse (122) gelagerten peristaltischen Pumpenrotoren (112, 114, 116, 118),

einem mit jedem der Pumpenrotoren ausgerichteter Laufring (130, 131) zum Eingriff flexibler Schläuche, um bei Drehung der Rotoren peristaltische Strömung hervorzurufen, einem separaten Motor (132, 134, 136, 138), der jeweils den peristaltischen Pumpenrotoren (112, 114, 116, 118) zugeordnet ist, und einem Antriebsmechanismus (140, 144, 152, 156, 128), um die Pumpenrotoren jeweils zum Betrieb mit einem anderen Motor anzuschliessen.

2. Pumpenmodulbaugruppe nach Anspruch 1, bei der mindestens einer der Laufringe (130) einzeln von seinem zugeordneten Rotor (112, 114, 116, 118) lösbar ist, so dass die Pumpwirkung seines zugeordneten Rotors unabhängig unterbrochen werden kann ohne dass die Pumpwirkung der anderen Rotoren dabei unterbrochen wird.

3. Pumpenmodulbaugruppe nach Anspruch 1, bei der die Laufringe von einer Abdeckung (104) gehalten werden, die zur Entnahme der Pumpenrotoren (112, 114, 116, 118), die an der einzelnen Achse (122) befestigt sind, in eine geöffnete Position bewegt werden kann.

4. Pumpenmodulbaugruppe nach Anspruch 3, bei der die Abdeckung (104) zwischen der geschlossenen und der geöffneten Position geschwenkt werden

kann.

5. Pumpenmodulbaugruppe nach einem der vorhergehenden Ansprüche, bei der der Antriebsmechanismus von den Motoren (132, 134, 136, 138) angetriebene Zahnradgetriebe (156) umfasst, und ein angetriebenes Zahnrad (128) jeweils mit jedem der Pumpenrotoren verbunden und so angepasst ist, dass es am Zahnradgetriebe angreift, wobei die angetriebenen Zahnräder (128) radial von den Zahnradgetrieben (156) getrennt werden können.

6. Pumpenmodulbaugruppe nach einem der vorhergehenden Ansprüche, eine Grundfläche umfassend, wobei jeder Pumpenrotor (112, 114, 116, 118) auf seinem Umfang umlaufend beabstandete Walzen (120) trägt, wobei sich jeweils mindestens ein Abschnitt jeden Pumpenrotors durch die Grundfläche erstreckt, wobei sich die Achse (122) parallel zu der Grundfläche erstreckt und die Walzen radial von der Grundfläche beabstandet sind.

7. Blutauflbereitungsvorrichtung mit:

einer Anordnung (20) von flexiblen Blutflussleitungen zum Transport von Blut, einer Pumpenmodulbaugruppe (100) nach Anspruch 1, wobei, jeder Rotor (112, 114, 116, 118) mit den Leitungen verbunden werden kann, um den Fluss des Blutes durch die Leitungen anzuregen, einem Gehäuse (102), das die Pumpenmodulbaugruppe (100) enthält, und eine abnehmbare Abdeckung (104) am Gehäuse, um die Pumpenmodulbaugruppe im Gehäuse zurückzuhalten, wenn die Abdeckung geschlossen ist, und um eine Entnahme der Pumpenmodulbaugruppe aus dem Gehäuse zuzulassen, wenn die Abdeckung geöffnet ist.

8. Pumpenmodulbaugruppe nach Anspruch 6, bei der der Antriebsmechanismus eine Welle (154) umfasst, die sich durch eine in einer Oberfläche des Gehäuses (102) befindliche Dichtung erstreckt, wobei die Pumpenmodulbaugruppe (100) von den Motoren (132, 134, 136, 138) als eine Einbaueinheit getrennt ist.

Revendications

1. Ensemble de modules de pompage comprenant:

au moins deux rotors de pompage péristaltique axialement alignés (112, 114, 116, 118) montés de façon tournante côte à côte sur un même arbre (122), un chemin de roulement (130, 131) aligné avec

chacun des rotors de pompage de manière à être en contact avec un tube souple pour engendrer une circulation péristaltique lors de la rotation des rotors, un moteur séparé (132, 134, 136, 138) associé à chacun des rotors de pompage péristaltique (112, 114, 116, 118), et un mécanisme d'entraînement (140, 144, 152, 156, 128) pour relier fonctionnellement chacun des rotors de pompage à un moteur différent des dits moteurs.

2. Ensemble de modules de pompage selon la revendication 1, dans lequel au moins un des chemins de roulement (130) est individuellement libérable de son rotor associé (112, 114, 116, 118) de sorte que l'action de pompage de son rotor de pompage associé peut être interrompue de façon indépendante sans interrompre l'action de pompage des autres rotors.

3. Ensemble de modules de pompage selon la revendication 1, dans lequel les chemins de roulement sont portés par un couvercle (104) qui est déplaçable à une position ouverte pour permettre l'enlèvement des rotors de pompage (112, 114, 116, 118) montés sur le même arbre (122).

4. Ensemble de modules de pompage selon la revendication 3, dans lequel le couvercle (104) peut pivoter entre la position fermée et la position ouverte.

5. Ensemble de modules de pompage selon une quelconque des revendications précédentes, dans lequel le mécanisme d'entraînement comprend des pignons d'entraînement (156) entraînés par les moteurs (132, 134, 136, 138), et un pignon entraîné (128) est attaché à chacun des rotors de pompage et agencé de manière à engrener avec le pignon d'entraînement, les pignons entraînés (128) étant radialement séparables des pignons d'entraînement (156).

6. Ensemble de modules de pompage selon une quelconque des revendications précédentes, incluant une surface de base, chaque rotor de pompage (112, 114, 116, 118) portant des galets (120) circumférentiellement espacés autour de sa périphérie, au moins une portion de chaque rotor de pompage s'étendant à travers la surface de base, l'arbre (122) étant parallèle à la surface de base et les galets étant espacés radialement de l'arbre.

7. Appareil de traitement du sang comprenant :

un ensemble (20) de conduits souples de circulation de sang, pour transporter le sang, un ensemble de modules de pompage (100)

selon la revendication 1, chaque rotor (112, 114, 116, 118) pouvant attaquer les conduits pour engendrer la circulation de sang dans les conduits,

un carter (102) contenant l'ensemble de modules de pompage (100), et 5

un couvercle amovible (104) placé sur le carter pour retenir l'ensemble de modules de pompage dans le carter lorsque le couvercle est fermé, et pour permettre l'enlèvement de l'ensemble de modules de pompage hors du carter lorsque le couvercle est ouvert. 10

8. Ensemble de modules de pompage selon la revendication 6, dans lequel le mécanisme d'entraînement comprend un arbre (154) s'étendant à travers une garniture d'étanchéité placée dans une surface du carter (102), de sorte que l'ensemble de modules de pompage (100) est séparé des moteurs (132, 134, 136, 138) comme un ensemble solidaire. 15 20

25

30



35


40


45



50

55












Fig. 10




Fig. 11




Fig. 9




Fig. 12.




Fig. 13




Fig. 14

15




Fig. 15

16




Fig. 16